

One way cassette

فن کویل کاستی یکطرفه



شرکت Goldman، نسل جدید فن کویل Clima cool خود را با فن آوری نوین مصرف انرژی ارائه کرده است

ظرفیت : ۳۰۰ تا ۶۰۰ فوت مکعب

ایجاد جریان یکنواخت و مطبوع




مطابق با استاندارد های روز اروپا Eurovent

دارای پمپ تخلیه آب

قابلیت درین تا ارتفاع ۷۵ سانتی متر

دارای فن سه دور و حالت اتوماتیک

- سطح صدای بسیار پایین
- مطابق با اصول معماری داخلی
- دارای راندمان بالا
- کوتاه ترین فن کویل روز دنیا





Model GLKC-				300	400	600
Air flow	H/M/L	m ³ /h	510/450/400	630/560/500	1000/880/800	
	H/M/L	CFM	300/270/240	370/330/300	590/520/470	
Cooling	Capacity	H/M/L	kW	3.04/2.79/2.56	3.79/3.58/3.38	5.709/4.85/4.36
	Water flow rate	H	l/h	520	650	982
	Water pressure drop	H	kPa	14	20	20.2
Heating	Capacity	H/M/L	kW	5.13/4.69/4.04	6.41/5.86/5.11	9.6/8.36/7.48
	Water pressure drop	H	kPa	9	16	18.1
Power supply		V/ph/Hz	220-240/1/50			
Power input	H	W	32	40	125	
Electric heater capacity (A)		W	750	750	/	
Sound pressure level	H/M/L	dB(A)	36/34/32	37/35/34	40/38/36	
Fan motor	Type	Low noise 4-speed fan motor				
	Quantity	1				
Fan	Type	Cross blow fan		Centrifugal, forward-curved Blades		
	Quantity	1		4		
Coil	Row	2		3		
	Max. Working pressure	MPa	1.6			
	Diameter	mm	φ7	φ8		
Panel	Dimensions	WxHxD	mm	1180x25x465	1420x10x755	
	Packing	WxHxD	mm	1232x107x517	1500x110x870	
	Net weight	kg	3.5	9		
	Gross weight	kg	5.2	12		
Body	Dimensions	WxHxD	mm	1054x169x425	1200x198x655	
	Packing	WxHxD	mm	1155x245x490	1380x265x720	
	Net weight	*/A	kg	12.8/13.1	32.6	
	Gross weight	*/A	kg	16.6/17.1	36.3	
Pipe connection	Water inlet/outlet pipe	Inch	RC1/2			
	Drain pipe	mm	ODφ25			

Note:

1. H: high fan speed; M: medium fan speed; L: low fan speed.
2. Cooling conditions: entering water 7 °C, temperature rise 5 °C, entering air temperature 27 °C DB/19 °C WB.
3. The noise is tested in the semi-anechoic test room.
4. * for models without electric heater, A for models with electric heater.